

Index

A

- active orthosis, 169, 171-174, 178-185, 187-189
- AFM system model, 106
- analog angular sensors, 69-99
- assistive devices, 195-197
- assistive/rehabilitative (AR), 197, 202
- atomic force microscopy (AFM), 103-107, 115, 117-119, 128-129
- automated identification, 133, 134, 164

B

- biomechanics of gait, 172

C

- Cartesian-type robot, 1, 21-23, 26
- computer-aided design/computer-aided manufacturing (CAD/CAM), 1, 2, 8, 11, 16, 17, 19-20, 26, 27
- control of mechatronics systems (COMES), 104-105, 111-113, 128
- control system, 10, 22-25, 27, 29, 33, 50-52, 54-55, 58, 64
- controller parameter space, 110

- correction tools, 94-95, 99

D

- decoding for identification, 139
- design criteria, 179
- dual-threshold method, 150

E

- electromagnetic induction technology, 161
- electromechanical coupling, 34, 38
- electromechanical IPMC model, 33-34
- envelope differential composite method, 155-156, 164
- experimental validation, 46

F

- finishing experiment, 25-26
- five-axis NC machine tool, 1-5
- fixed-period delay method, 158, 160, 164
- force feedback loop, 11-12, 20, 22-23
- frequency characteristic, 24-25
- fuzzy control, 214-216, 219, 221, 229

G

- gain schedule, 58, 60
- gait rehabilitation, 169, 171-172, 174, 179, 185-186, 189
- gait training, 169-173, 175-178, 181, 184, 189

I

- identification technology, 133-134, 136
- industrial robot, 1, 8-9, 12-13, 16-18, 20, 26-27
- ionic polymer-metal composite (IPMC), 29-41, 43-52, 54-56, 59-61, 63-64
- IPMC stepper motor, 44-45, 49

K

- knee exoskeleton, 195, 202-204

L

- laser light emission, 134, 144-145, 164
- LED lens mold, 21-26

M

- manufacturing purposes, 69
- mathematical model, 69, 72-73, 75, 77, 83, 88-89, 99
- mechanical beam model, 34, 39
- mechanical design, 29, 33, 39, 45, 50, 63
- mechatronics applications, 29
- mechatronics systems, 1, 26
- microwave transmission technology, 162
- mixed sensitivity, 109-111, 113, 129
- model integration and simulation, 46
- modeling and control, 29, 63

- modeling and simulation, 69-99
- mold finishing, 16, 26
- multi-line scan, 144-145, 163-164

N

- nonlinear controller, 58
- nonlinear electric circuit, 34-36

O

- overall model, 94

P

- pancake resolver model, 73, 79-81, 84
- PID controller, 55, 58, 60-61
- piezotube, 105, 107-108, 113, 115, 117-120, 122, 124-129
- PMA dynamic modeling, 182
- pneumatic artificial muscle (PAM), 195, 199, 200, 202-211, 215-217, 219, 221-224, 228-232
- pneumatic muscle actuators (PMA), 169, 179-183, 187-189
- position feedback loop, 11-12, 19, 20, 22-23
- post-processor, 2-7, 9

R

- radio frequency identification technology (RFID), 133-134, 160-164
- rehabilitation robotics, 170
- repetitive control, 103-105, 108-113, 115-117, 128-129
- robot-assisted gait, 170-174, 176, 178, 181, 184-185
- robotic rotary joint, 29, 43, 49
- robust control, 103, 105, 108, 117, 128
- rotary unit, 1, 4-7, 26

S

scanning technology, 142, 164
self-organizing fuzzy controllers
(SOFC), 220-224, 229-230
serial binary barcode, 134, 136, 139,
163-164
solenoid valve, 203-204, 211
surface electromyography (sEMG),
199-200, 203-204, 224-228, 231
system parameter tuning, 51

T, W

tapping mode, 104-106
ternary barcode, 134, 149-152,
156-157, 164-165
three-axis NC machine tool, 1, 4-7,
26
tilting head, 1-5, 26
two-dimensional binary barcode,
140, 164
wooden workpiece, 7-9