

## Index

### a

- acid/base catalysis 26
- acoustic fluid shaking 157
- active micromixers
  - acoustic fluid shaking 157
  - alternating current magnetohydrodynamic (MHD) actuation 158
  - electrowetting-induced droplet shaking 156
  - elektrokinetic instability 155
  - microstirrers 157
  - pressure induced disturbances 154
  - ultrasound/piezoelectric membrane action 156
- active micromixing 144
- adiabatic temperature rise
  - multi-injection microstructured reactors 214
  - single-injection micro-structured reactors 218
- alternating current magnetohydrodynamic (MHD) actuation 158

### b

- batch reactors 1
- batch-wise operated stirred tank reactor (BSTR)
  - Damköhler number 32
  - heat balance 30
  - intermediate product yield
    - vs. Damköhler number 34
  - mass balance 30
  - reaction time 31
  - reactor performance 31
- bimolecular catalytic reactions 56
- Bodenstein number 102, 126
- BSTR *see* Batch-wise operated stirred tank reactor (BSTR) 30

- bubble columns 268
- bubbly flow 273

### c

- C-curve 93, 95
- Carberry number 64
- catalytic gas-phase reactions
  - catalytic wall micro-reactors 238
    - characteristics 238
  - randomly micro-packed bed reactors
    - advantage 233
    - backmixing 233
    - flow mal-distribution 233
    - integrated packed bed-heat exchanger 234
      - reaction slit and cooling channels 234
      - residence time distribution 233
      - shallow micro-fabricated channels 233
      - silicon cross-flow microreactor 234
    - structured catalytic micro-bed reactors
      - catalytic filaments 236
      - endothermic steam-reforming 235
      - integrated exchangeable catalytic foam plates 237
      - membrane reactor 236
      - metallic/ceramic foams 236
      - micro-structured string-reactor 235
      - parallel filaments 235
      - residence time distribution 235
      - sintered metal fibers (SMF) 238
      - slit-like channels 237
  - catalytic wall micro-reactors 238
    - Damköhler number 249, 250
    - heat transfer 250
    - hydrodynamic entrance zone length 246
    - internal effectiveness factor 246
    - mass transfer characteristics 247
    - mass transfer coefficient 247

catalytic wall micro-reactors (*contd.*)

- quasi-isothermal behavior 246
- Sherwood numbers 247
- zero-order reaction 249
- caterpillar micromixer 149
- chaotic mixing 143, 149
- characteristic mixing time 129
- characteristic reaction time 3
- chemical reactors
  - continuum models 180
  - heat balance 180
  - heat management 179
  - material balance 180
  - temperature range selection 179
- Chilton-Colburn analogy 66, 82
- Churn flow 279
- Coanda effect micromixer 153
- complete segregation 130
- complex microchannel geometries 191
- constant density reactions
  - CSTR 37
  - PFR 40
- continuous flow microstructured reactors 286
- continuous stirred tank reactor (CSTR)
  - constant density reactions 37
  - conversion *vs.* Damköhler number 38
  - degree of backmixing 35
  - heat balance 38
  - mass balance 36
  - space time 36
  - variable density reactions 37
- continuous-stirred tank reactor (CSTR)
  - RTD 95
- continuum models 180
- conversion 29
- CSTR *see* Continuous stirred tank reactor (CSTR) 35
- curved microchannels 189
- cyclone mixer 269, 270

**d**

- Damköhler number 115, 132
  - BSTR 32, 34
  - PFR 43
  - *vs.* isothermal external effectiveness factor 63
- Dean number 145
- deformed interface flow 282, 297
- dispersed flow 283, 298
- dispersion model 101, 111
- dry etching 10

**e**

- effective heat exchange area 185
- effective reaction rate 196
- efficient instantaneous catalyst selectivity 76
- electrowetting-induced droplet shaking 156
- elektrokinetic instability micromixer 155
- energetic efficiency of mixing 172
- energy balance 20
- Engulfment flow 144
- enzymatic catalysis 27
- external numbering up 8

**f**

- F* curve 92, 95
- falling film contactors 268
- Fischer-Tropsch synthesis 261
- flow separators
  - conventional separators 308
  - geometrical modifications 309
  - gravity based separation 315
  - IMM settler 315
  - wettability
    - – contact angles 310
    - – flow resistance 314
    - – hydrophilic and hydrophobic material 310
    - – membrane separator 311, 312
    - – pressure drop 312, 313
    - – Y-shaped separator 311
- fluid-fluid microstructured reactors
  - conventional reactors
    - – advantages and disadvantages 268, 269
    - – applications 267
    - – equipments 267
    - – gas-liquid mass transfer 267
    - – liquid-liquid reactions 267
    - – multiphase microstructured devices 268
  - falling film reactor 272
  - flow separation *see* Flow separators 307
  - gas-liquid flow patterns
    - – annular and parallel flow 280
    - – bubbly flow 273
    - – churn flow 279
    - – classification 273
    - – slug-bubbly flow 279
    - – Taylor flow *see* Taylor flow 274
  - gas-liquid reactions
    - – halogenation 317
    - – hydrogenation 319
    - – nitration 318
    - – oxidation 318
    - – sulfonation 318
  - Hatta number 316
  - liquid-liquid flow patterns

- – annular and parallel flow 283
  - – classification 280
  - – deformed interface flow 282
  - – dispersed flow 283
  - – drop flow 281
  - – slug flow 281
  - – slug-dispersed flow 283
  - – slug-drop flow 282
  - liquid-liquid reactions
    - – benzene nitration 319
    - – biodiesel production 320
    - – enzymatic reactions 322
    - – PTC 321
    - – toluene nitration 319
    - – vitamin precursor synthesis 320
  - mass transfer *see* Mass transfer 284
  - microchannels
    - – inlet T Y and concentric contactor 271
    - – mesh/sieve-like interfacial support contactors 271
    - – parallel 272
    - – partial two fluid contact 271
    - – static mixers 272
  - micromixers 269
  - pressure drop *see* Pressure drop 300
  - fluid-solid micro-structured reactors
    - advantages and disadvantages 232
    - catalytic dehydration 259
    - catalytic partial oxidations
      - – ammonia oxidation 255
      - – chip-like reactor 257
      - – H<sub>2</sub>/O<sub>2</sub> oxidation reaction 256
      - – methane 256
      - – quartz glass micro-reactor 256
      - – silicon membrane microreactor 255
      - – T-shaped microchannel 255
    - ethylene oxide synthesis 259
    - exothermic/endothemic reactions 232
    - Fischer–Tropsch synthesis 261
    - hydrodynamics
      - – Ergun equation 240
      - – geometric factor 242
      - – Hagen–Poiseuille equation 242
      - – Knudsen coefficient 240
      - – mono-sized spherical particles 240
      - – particle size distribution 240
      - – pressure drop 239–241
      - – surface area per foam volume 241, 243
    - mass transfer
      - – catalytic foam micro-reactors 245
      - – catalytic wall micro-reactors *see* Catalytic wall micro-reactors 246
      - – Damköhler number 244
      - – external and internal 244
      - – randomly – packed bed catalytic micro-reactor 244
      - – reactor selection 253
      - parallel flow channels 232
      - steam reforming 260
      - types 231, 232
    - formal kinetic equations
      - Homogeneous Catalytic Reactions 26
      - multiple homogeneous reactions 24
      - Single Homogeneous Reactions 22
    - fractional surface coverage 51
- g**
- gas-liquid-liquid systems 346
  - gas-liquid-solid systems
    - continuous phase microstructured reactors
      - – mesh microcontactor 333–335
      - – microstructured falling film reactor 333
    - conventional reactors 331
    - dispersed phase microstructured reactors
      - – microbubble column 335
      - – microstructured packed bed reactor 335
      - – segmented flow gas-liquid-solid reactors 335
      - – Taylor flow 334
    - mass transfer and chemical reaction
      - – catalytic microstructured film reactor 337, 338
      - – concentration profiles 336
      - – global transformation rate 336
      - – hydrodynamic characteristics 340
      - – hydrogenation 341
      - – interfacial area 339
      - – irreversible reaction 336
      - – mass transfer coefficient 338
      - – mass transfer rate 337
      - – mass transfer resistance 341
      - – mesh microcontactor 339
      - – observed reaction rate 338
      - – reaction rate per unit 336
      - – segmented flow gas-liquid-solid reactors 340
      - – volumetric mass transfer 340
    - reaction examples
      - – catalyst deactivation 345
      - – catalytic hydrogenations 341
      - – cyclohexene hydrogenation 346
      - – heterogeneous hydrogenation 345
      - – low liquid and gas velocities 346
      - – micro packed beds 344
      - – microfabricated structured catalyst packing 345
      - – silicon/glass microreactors 346
      - – types of reactions 342

**h**

- Hagen–Poiseuille equation 140
  - Hatta number 45, 316
  - heat balance
    - BSTR 30
    - chemical reactors 180
    - CSTR 38
    - MSR 198
    - PFR 44
  - heat transfer
    - complex geometries 191
    - curved channels 189
    - multichannel micro heat exchanger
      - axial temperature profiles 192
      - heat exchanger efficiency 192
    - straight microchannels
      - aspect ratio *vs.* asymptotic Nusselt number 184
      - asymptotic Nusselt- and Sherwood-numbers 183
      - effective heat exchange area 185
      - laminar velocity profile 182
      - mean Nusselt number 183
      - overall heat transfer coefficient 182
      - shell and tube micro heat exchanger 186
      - two phase flow system
        - flow rate *vs.* Nusselt number 195
        - Nusselt number 194
        - *vs.* single phase flow 194
  - helicoidal microchannel falling-film reactor 273, 293
  - heterogeneous catalytic reactions
    - advantages 49
    - bimolecular catalytic reactions 56
    - concentration profiles 60
    - isothermal external effectiveness factor
      - *vs.* Carberry number 64
      - *vs.* Damköhler number 63
      - yield and selectivity 64
    - isothermal internal effectiveness factor
      - *vs.* generalized Thiele modulus 71
      - *vs.* generalized Weisz modulus 73
      - *vs.* Thiele modulus 69
      - selectivity and yield 74
    - Langmuir adsorption isotherms 51
    - Langmuir–Hinshelwood model 53
    - most abundant surface intermediate (MASI) approximation 55
    - non-isothermal external effectiveness factor 67
    - physical and chemical steps 59
    - quasi-surface equilibrium approximation 54
    - rate equations 50
      - rate of deactivation 58
      - transport effects estimation criteria 83
  - heterogeneous reactions
    - mass- and heat transfer 20
  - homogeneous catalytic reactions 26
    - biphasic systems
      - catalyst recovery 45
      - fast chemical reaction 47
      - moderate chemical reaction 46
      - reactor efficiency *vs.* Hatta number 48
      - slow chemical reaction 45
      - SLP catalysts 49
    - drawback 45
    - formal Kinetics 26
  - homogeneous reaction 4
    - multiple reactions 24
    - single reaction 22
  - homogeneous reactions
    - definition 85
    - mass- and heat transfer 20
    - reaction mechanism 25
- i**
- ideal reactors
    - BSTR *see* Batch-wise operated stirred tank reactor (BSTR) 30
    - CSTR *see* Continuous stirred tank reactor (CSTR) 35
    - performance parameters 29
    - PFR *see* plug flow reactor (PFR) 39
    - types 29
  - instantaneous selectivity 30
  - intensity of segregation 130, 158
  - interdigital micromixers 147
  - interdigital mixer 269, 270
  - interexchange with mean (IEM) model 166
  - international Conference on Microreaction Technology (IMRET) 11
  - international Union of Pure and Applied Chemistry (IUPAC) 22
  - introduction 1
- j**
- jet micromixer 151
- k**
- Knudsen coefficient 180
- l**
- Langmuir adsorption isotherms 51
  - Langmuir–Hinshelwood model 53
  - LIGA process 9

**m**

- macroscopic mixing 129
- mass balance
  - BSTR 30
  - CSTR 36
  - PFR 39
- mass Biot number 79
- mass transfer
  - characterization 286
  - film-penetration model 285
  - gas-liquid microstructured devices
    - – microstructured falling film reactors *see* Microstructured falling film reactors 293
    - – slug-annular and churn flow regime 292
    - – Taylor flow *see* Taylor flow, mass transfer 287
  - liquid-liquid microstructured devices
    - – annular and parallel flow 297
    - – deformed interface flow 297
    - – dispersed flow 298
    - – slug flow 296
    - – slug-dispersed flow 298
    - – slug-drop flow 297
  - liquid-side mass transfer coefficients 285
  - macro-model 285
  - micro-models 285
  - non-reactive systems 284
  - penetration model 285
  - reactive systems 284
  - vs. conventional contactors 299
- material balance 19
  - chemical reactors 180
  - MSR 197
- MBT device *see* Microfluidic baker's transformation (MBT) device 153
- mean residence time 91
- meander mixer 146
- mesh microcontactor 333, 335, 339
- Michaelis-Menten model 27, 85
- micro bubble column 317
- micro-channels
  - laminar flow mixing
    - – characteristic dimension 138
    - – characteristic mixing time 141
    - – engulfment regime 142
    - – predicted vs. experimentally determined mixing time 141, 142
    - – pressure drop 140
    - – specific power dissipation 140
    - – T-mixer 136
    - – time for diffusion 137
  - RTD
    - – axial and radial diffusion 115
    - – gas flow 117
    - – liquid flow 118
    - – multiphase flow 122
- micro-electrical discharge machining 10
- microchannels
  - inlet T Y and concentric contactor 271
  - mesh/sieve-like interfacial support contactors 271
  - parallel 272
  - partial two fluid contact 271
  - static mixers 272
- microfluidic baker's transformation (MBT) device, 153
- micromixers 269
  - active mixers *see* Active micromixers 154
  - efficiency characterization
    - – absorbance vs. Reynolds number 170
    - – chemical methods 159
    - – competitive neutralisation and acetal hydrolysis 161
    - – consecutive and parallel competitive reactions 160
    - – dependent factors 158
    - – diazo coupling reactions 161
    - – energetic efficiency of mixing 172
    - – flow rate vs. segregation index 166
    - – mixing time vs. absorbance 167
    - – mixing time vs. Reynolds number 171
    - – mixing time vs. specific power dissipation 169
    - – mixing time vs. specific power dissipation 169
    - – neutralization and ester hydrolysis reactions 160
    - – optical techniques 159
    - – physical methods 158
    - – segregation index 163
    - – Villermaux-Dushman reaction 162
  - passive mixer *see* Passive micromixers 144
  - passive vs. active mixing 143
  - schematic representation 144
- microscopic mixing 129
- microstirrers 157
- microstructured falling film reactor 272, 317, 333, 334
  - disadvantage 293
  - mass transfer coefficient 294
  - mass transfer resistance 293
  - microchannels 293, 294
  - surface structure 296
- microstructured reactors (MSR)
  - 1-ethyle-3-methyle imidazolium ethyl sulfate synthesis 207
  - advantages

- microstructured reactors (MSR) (*contd.*)
    - – novel operating window 7
    - – numbering-up 7
    - – process safety 5
    - – transfer rates 2
    - applications 10
    - axial temperature profile 199
    - benchmarking 5
    - chemical mobile plants 12
    - chemical reactions categories of, 195
    - energy balance 198
    - fabrication techniques 9
    - fine chemical/pharmaceutical industry 12
    - fluid-fluid reactors, *see* Fluid-fluid microstructured reactors 267
    - heat evacuation 196
    - hotspot reduction strategies 196
    - laboratory tool 11
    - material balance 197
    - multi-injection *see* Multi-injection microstructured reactors 212
    - objectives 2
    - overall heat transfer coefficient 199
    - parametric sensitivity 201
    - selection steps 9
    - single-injection *see* Single-injection microstructured reactors 218
    - vs. conventional processing 13
  - miniaturized systems 2
  - mixer-settler 269
  - most abundant surface intermediate (MASI) approximation 55
  - moving droplet mixers 151
  - multi-injection microstructured reactors
    - adiabatic temperature rise 214
    - Grignard reaction 224
    - heat balance 213
    - heat evacuation time 213
    - hot-spot reduction
      - – number of injection points 218
      - – unequal flow partition 219
    - mass balance 213
    - schematic representation 213
    - temperature profile 217
  - multichannel micro heat exchanger
    - axial temperature profiles 192
    - heat exchanger efficiency 192
  - multilamination mixers
    - bifurcation-type feeds 147
    - cyclone mixer 148
    - interdigital mixers 147
    - SuperFocus mixers 148
  - multiple homogeneous reactions 24
  - multiple reactions 22
- n**
- novel operating windows 7
  - nucleophilic/electrophilic catalysis 26
  - numbering-up strategy 8
  - Nusselt falling film theory 338
- o**
- organometallic complex catalysis 26, 27
  - overall volumetric heat transfer coefficient 191
- p**
- parallel microchannels 272
  - passive micromixers
    - chaotic mixing 149
    - Coanda effect mixer 153
    - integrated mixer/valve design 153
    - jet collision device 150
    - MBT 153
    - moving droplet mixers 151
    - multilamination mixers
      - – bifurcation-type feeds 147
      - – cyclone mixer 148
      - – interdigital mixers 147
      - – SuperFocus mixers 148
      - – types 147
    - SAR mixers 149
    - single channel mixers
      - – cyclone type mixers 145
      - – T-mixer 144
    - structured packing 149, 150
  - passive micromixing 143
  - PFR *see* Plug flow reactor (PFR) 39
  - phase transfer catalysis (PTC)
    - $\beta$ -keto esters 321
    - p-nitrophenyl acetate hydrolysis 321
  - plug flow reactor (PFR)
    - constant density reactions 40
    - conversion vs. Damkohler-number 43
    - heat balance 44
    - mass balance 39, 198
    - mixing
      - – Damkohler number 132
      - – fast mixing 133
      - – intermediate yield vs. conversion 134
      - – mass balances 133
      - – segregation intensity 131
      - – slow mixing 132
    - reactor volume and space time 39
    - RTD 95
    - variable density reactions 41
  - power rate law (PRL) 22, 25
  - Prater number 77, 78
  - pressure drop

- gas-liquid flow
    - – homogenous model 301
    - – separated flow model 301, 302
  - liquid-liquid flow
    - – power dissipation 307
    - – with film 305
    - – without film 304
  - PRL *see* Power Rate Law (PRL) 25
  - process classification 1
  - process safety 5
  - pulse function stimulus- response method 93
- q**
- quasi steady-state approximation (QSSA) 26
  - quasi-surface equilibrium approximation 54
- r**
- randomly–packed bed catalytic micro-reactor
    - gas-phase reactions
      - – advantage 233
      - – backmixing 233
      - – flow mal-distribution 233
      - – integrated packed bed-heat exchanger 234
      - – reaction slit and cooling channels 234
      - – residence time distribution 233
      - – shallow micro-fabricated channels 233
      - – silicon cross-flow microreactor 234
    - mass transfer 244
  - rate determining step approach 25
  - reaction orders 22
  - reactor volume
    - CSTR 36
    - PFR 39
  - residence time distribution (RTD)
    - cascade CSTR 96
    - CSTR 95
    - dispersion model 101
    - experimental determination
      - – pulse function stimulus- response method 93
      - – step function stimulus- response method 92
    - function  $E(t)$  90
    - idealvs. real reactors 96, 97
    - micro-channel reactors
      - – axial and radial diffusion 115
      - – gas flow 117
      - – liquid flow 118
      - – multiphase flow 122
    - PFR 95
    - reactor performance
      - – dispersion model 111
      - – known formal kinetics 108
      - – positive reaction order 107
      - – product yield 114
      - – tanks-in-series model 112
    - real reactors, models for
      - – dispersion model 101
      - – tanks-in-series model 100
    - tanks-in-series model 100
    - tubular reactors
      - – axial dispersion estimation 105
      - – boundary conditions 102
      - – laminar flow 98
      - – pulse function stimulus-response method 94
  - Reynolds-number 283
  - RTD *see* Resident time distribution (RTD) 90
- s**
- SAR mixers *see* Split-and-recombine (SAR) mixers 148
  - segmented flow
    - Nusselt number 194
  - segmented flow gas-liquid-solid reactors 340
  - segregation 130
  - selectivity 30
  - shell and tube micro heat exchanger 186
  - single channel mixers
    - cyclone type mixers 145
    - T-mixer 144
  - single homogeneous reactions 22
  - single reaction 22
  - single-injection micro-structured reactors
    - 1,3-Dimethylimidazolium-triflate synthesis 221
    - adiabatic temperature rise 218
    - dialkyl-substituted thioureas nitration 222
    - methyl butyrate reduction 223
  - sinusoidal corrugated-plate channels 189, 190
  - skewness 91
  - SLPC *see* Supported liquid phase catalysis (SLPC) 49
  - slug flow, *see also* Taylor flow 274, 281, 296
  - slug-bubbly flow 279
  - slug-dispersed flow 298
  - slug-drop flow 282, 297
  - slug-flow micro-reactor 11
  - space time
    - CSTR 36
    - PFR 40
  - specific heat production 196
  - split-and-recombine (SAR) mixers 148
  - staggered herringbone mixer (SHM) 151

- stagnant film model 285
- star lamination micromixer 148
- step function stimulus- response method 92
- stirred tanks 268
- straight microchannels
  - aspect ratios. asymptotic Nusselt number 184
  - effective heat exchange area 185
  - laminar velocity profile 182
  - mean Nusselt number 183
  - overall heat transfer coefficient 182
  - shell and tube micro heat exchanger 186
- stratified flow 144
- streamlined fins 296
- SuperFocus micromixer 148
- supported liquid phase catalysis (SLPC) 49
- system volume 19
  
- t**
- T-mixer
  - design 169
  - flow regimes 144
- tanks-in-series model 100, 112
- Taylor flow
  - applications 276
  - bubble velocity 277, 278
  - capillary number 276
  - correlations 276
  - delay tube 274
  - flow rates and fluid properties 276
  - generation 275
  - interfacial gas–liquid area 276
  - mass transfer
    - – caps and liquid film 290
    - – characteristic diffusion time 291
    - – film contact time 291
    - – film mass transfer coefficient 289
    - – gas-liquid mass transfer 287, 288
    - – Higbie penetration model 287
    - – liquid slug lengths 290
    - – superficial gas velocity 290
    - – Taylor bubbles 287
  - radial mixing 276
- Thiele modulus 70
- three phase systems
  - gas-liquid-liquid systems 346
  - gas-liquid-solid systems 331
  - hydrodynamics 331
- Train flow *see* Taylor flow 274
- trans-esterification 320
- tubular contactors 268
- tubular reactors
  - axial dispersion estimation 105
  - boundary conditions 102
  - laminar flow 98
  - pulse function stimulus-response method 94
  
- v**
- variable density reactions
  - CSTR 37
  - PFR 41
- Villermaux-Dushman reaction 162
- Vortex flow 144
  
- w**
- Weisz modulus 72
- wet etching 10
  
- y**
- yield 29